

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

SECTION 1. IDENTIFICATION

Product name : Buserelin Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)


Hazards for the product as supplied

Skin sensitization : Category 1

Other hazards

None known.

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H317 May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
P261 Avoid breathing mist or vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Benzyl alcohol	100-51-6*	$\geq 1 - \leq 5$	TSC
Buserelin	68630-75-1*	$> 0 - \leq 0.1$	TSC

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.
Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material.
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

- Local/Total ventilation : Use only with adequate ventilation.
Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapors.
Do not swallow.
Avoid contact with eyes.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:
Strong oxidizing agents
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
Buserelin	68630-75-1	TWA	0.1 µg/m ³ (OEB 5)	Internal
		Wipe limit	1 µg/100 cm ²	Internal

- Engineering measures** : The information below is intended for larger pilot/commercial-scale operations and manufacturing. For smaller scale, clinical, or pharmacy settings, site-specific internal risk assessment practices should be conducted to determine appropriate exposure control measures. The health hazard risks of handling this material are dependent on multiple factors, including but not limited to physical form and quantity handled. If applicable, use process enclosures, local exhaust ventilation (e.g., Biosafety Cabinet, Ventilated Balance Enclosures), or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels as low as reasonably achievable.
- Use closed processing systems or containment technologies to control at source (e.g., glove boxes/isolators) and to prevent leakage of compounds into the workplace.
- All engineering controls should be implemented by facility design and operated in accordance with GMP principles to protect products, workers, and the environment.
- No open handling permitted.
- Totally enclosed processes and materials transport systems are required.
- Operations require the use of appropriate containment technology designed to prevent leakage of compounds into

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

the workplace.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Consider double gloving.

Eye protection : Wear safety glasses with side shields or goggles. If the work environment or activity involves dusty conditions, mists or aerosols, wear the appropriate goggles. Wear a faceshield or other full face protection if there is a potential for direct contact to the face with dusts, mists, or aerosols.

Skin and body protection : Work uniform or laboratory coat. Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces. Use appropriate degowning techniques to remove potentially contaminated clothing.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before re-use. The effective operation of a facility should include review of engineering controls, proper personal protective equipment, appropriate degowning and decontamination procedures, industrial hygiene monitoring, medical surveillance and the use of administrative controls.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid, Aqueous solution

Color : colorless

Odor : No data available

Odor Threshold : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

pH : 5.7 - 6.3

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : No data available

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : 1.004 g/cm³

Solubility(ies)
Water solubility : soluble

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : Not applicable

Decomposition temperature : No data available

Viscosity
Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : Not applicable

Particle characteristics
Particle size : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : Can react with strong oxidizing agents.
Conditions to avoid : None known.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg
Method: Calculation method

Components:

Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Buserelin:

Acute oral toxicity : LD50 (Rat): 400 mg/kg
LD50 (Mouse): > 1,000 mg/kg
Acute toxicity (other routes of administration) : LD50 (Rat): 36 mg/kg
Application Route: Intravenous
LD50 (Rat): > 500 mg/kg
Application Route: Subcutaneous
LD50 (Mouse): 56 - 78 mg/kg
Application Route: Intravenous

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

LD50 (Dog): > 100 mg/kg
Application Route: Subcutaneous

Skin corrosion/irritation

Not classified based on available information.

Components:

Benzyl alcohol:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation

Buserelin:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Benzyl alcohol:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Method : OECD Test Guideline 405

Buserelin:

Species : Rabbit
Result : No eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

Benzyl alcohol:

Test Type : Human repeat insult patch test (HRIPT)
Routes of exposure : Skin contact
Species : Humans
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitization rate in humans

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

Buserelin:

Routes of exposure : Dermal
Species : Guinea pig
Result : Not a skin sensitizer.

Germ cell mutagenicity

Not classified based on available information.

Components:

Benzyl alcohol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Buserelin:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Test Type: unscheduled DNA synthesis assay
Result: negative
Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

Benzyl alcohol:

Species : Mouse
Application Route : Ingestion
Exposure time : 103 weeks
Method : OECD Test Guideline 451
Result : negative

Buserelin:

Species : Rat
Application Route : Subcutaneous
Exposure time : 24 Months
Result : negative
Target Organs : Uterus (including cervix), Pituitary gland, Testes

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

Test Type: Embryo-fetal development
Species: Rabbit
Developmental Toxicity: LOAEL: 0.1 µg/kg body weight
Result: Embryotoxic effects., No specific developmental abnormalities.

Test Type: Embryo-fetal development
Species: Mouse
Developmental Toxicity: NOAEL: 0.1 µg/kg body weight
Result: Embryotoxic effects., No effects on F1 offspring.

Reproductive toxicity - Assessment : May damage fertility.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

Benzyl alcohol:

Species : Rat
NOAEL : 1.072 mg/l
Application Route : inhalation (dust/mist/fume)
Exposure time : 28 Days
Method : OECD Test Guideline 412

Buserelin:

Species : Rat
LOAEL : 0.5 ug/kg/day
Application Route : Subcutaneous
Exposure time : 14 Days

Species : Rat
LOAEL : 0.05 ug/kg/day
Application Route : Subcutaneous
Exposure time : 28 Days
Target Organs : Testis

Species : Rabbit
NOAEL : 20 ug/kg/day
Exposure time : 4 Weeks
Target Organs : Prostate, Pituitary gland, Testis

Species : Monkey
LOAEL : 5 ug/kg/day
Exposure time : 1 y
Target Organs : Ovary, Pituitary gland

Species : Dog

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

LOAEL : 0.05 mg/kg
Application Route : Subcutaneous
Exposure time : 30 Days
Target Organs : Pituitary gland, Testis

Species : Dog
LOAEL : 0.05 mg/kg
Application Route : Subcutaneous
Exposure time : 6 Months
Target Organs : Reproductive organs

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Buserelin:

Inhalation : Symptoms: male reproductive effects, female reproductive effects, reduced libido, Headache, Rash, Gastrointestinal disturbance, mental depression, Local irritation
Remarks: May damage fertility.
Based on Human Evidence

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Benzyl alcohol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 51 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version 13.0 Revision Date: 05/09/2026 SDS Number: 641714-00029 Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

Buserelin:

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Persistence and degradability

Components:

Benzyl alcohol:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 92 - 96 %
Exposure time: 14 d

Bioaccumulative potential

Components:

Benzyl alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.05

Mobility in soil

No data available

Other adverse effects

No data available

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01/21/2026
13.0	05/09/2026	641714-00029	Date of first issue: 05/03/2016

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5
Benzyl alcohol	100-51-6

The ingredients of this product are reported in the following inventories:

AICS : not determined

CA. DSL : not determined

CN IECSC : not determined

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation


Version
13.0

Revision Date:
05/09/2026

SDS Number:
641714-00029

Date of last issue: 01/21/2026
Date of first issue: 05/03/2016

NFPA 704:



HMIS® IV / CED:

HEALTH	/	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)
US WEEL / TWA : 8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Buserelin Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 01/21/2026
13.0	05/09/2026	641714-00029	Date of first issue: 05/03/2016

Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/09/2026

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8