

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

### SECTION 1. IDENTIFICATION

Product name : Bismuth Subnitrate Formulation

#### Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc  
Address : 126 E. Lincoln Avenue  
Rahway, New Jersey U.S.A. 07065  
Telephone : 908-740-4000  
Emergency telephone : 1-908-423-6000  
E-mail address : EHSDATASTEWARD@merck.com

#### Recommended use of the chemical and restrictions on use

Recommended use : Veterinary product  
Restrictions on use : Not applicable

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

#### Hazards for the product as supplied

Skin sensitization : Category 1  
Specific target organ toxicity : Category 1 (Central nervous system)  
- repeated exposure

#### Other hazards

None known.

#### GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P261 Avoid breathing dust, fume, gas, mist, vapors or spray.  
P264 Wash skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing must not be allowed out of the workplace.  
P280 Wear protective gloves.

**Response:**

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P314 Get medical attention if you feel unwell.  
P333 + P313 If skin irritation or rash occurs: Get medical attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

### Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)	Trade secret
Bismuth hydroxide nitrate oxide	1304-85-4*	>= 45 - <= 70	TSC
Petrolatum	8009-03-8*	>= 10 - <= 30	TSC
Zinc oxide	1314-13-2*	>= 3 - <= 7	TSC
Benzyl alcohol	100-51-6*	>= 0.5 - <= 1.5	TSC

\* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

### SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.  
Causes damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

Protection of first-aiders	:	First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
Notes to physician	:	Treat symptomatically and supportively.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	None known.
Specific hazards during fire fighting	:	Exposure to combustion products may be a hazard to health.
Hazardous combustion products	:	Nitrogen oxides (NOx) Metal oxides Carbon oxides
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.
Special protective equipment for fire-fighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
Environmental precautions	:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent. Local or national regulations may apply to releases and

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

### SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing.  
Avoid breathing dust, fume, gas, mist, vapors or spray.  
Do not swallow.  
Avoid contact with eyes.  
Wash skin thoroughly after handling.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
Do not eat, drink or smoke when using this product.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents  
Self-reactive substances and mixtures  
Organic peroxides  
Explosives  
Gases

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Petrolatum	8009-03-8	TWA (Mist)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m <sup>3</sup>	ACGIH
		TWA (Mist)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Mist)	10 mg/m <sup>3</sup>	NIOSH REL
Zinc oxide	1314-13-2	TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH
		STEL (Respirable particulate matter)	10 mg/m <sup>3</sup>	ACGIH

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

		TWA (Dust)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (Fumes)	5 mg/m <sup>3</sup>	NIOSH REL
		ST (Fumes)	10 mg/m <sup>3</sup>	NIOSH REL
		C (Dust)	15 mg/m <sup>3</sup>	NIOSH REL
		TWA (Fumes)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL

**Engineering measures** : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

### Personal protective equipment

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

### Hand protection

**Material** : Chemical-resistant gloves

**Remarks** : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

**Eye protection** : Wear the following personal protective equipment:  
Safety glasses

**Skin and body protection** : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

**Hygiene measures** : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
When using do not eat, drink or smoke.  
Contaminated work clothing should not be allowed out of the workplace.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

Wash contaminated clothing before re-use.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	paste
Color	:	white
Odor	:	Petroleum
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Flash point	:	Not applicable
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Flammability (liquids)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	No data available
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Particle characteristics  
Particle size : No data available

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : Can react with strong oxidizing agents.  
Conditions to avoid : None known.  
Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No hazardous decomposition products are known.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Skin contact  
Ingestion  
Eye contact

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

#### Components:

##### Bismuth hydroxide nitrate oxide:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 423  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.07 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 436  
Remarks: Based on data from similar materials

##### Petrolatum:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

### Zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,200 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.4 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

### Skin corrosion/irritation

Not classified based on available information.

### Components:

#### Bismuth hydroxide nitrate oxide:

Species : reconstructed human epidermis (RhE)  
Method : OECD Test Guideline 439

Result : No skin irritation

#### Petrolatum:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation  
Remarks : Based on data from similar materials

#### Zinc oxide:

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

### **Benzyl alcohol:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Components:**

#### **Bismuth hydroxide nitrate oxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

#### **Petrolatum:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

#### **Zinc oxide:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

### **Benzyl alcohol:**

Species : Rabbit  
Result : Irritation to eyes, reversing within 21 days  
Method : OECD Test Guideline 405

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

### **Components:**

#### **Bismuth hydroxide nitrate oxide:**

Test Type : Local lymph node assay (LLNA)  
Routes of exposure : Skin contact  
Species : Mouse  
Method : OECD Test Guideline 429  
Result : negative

#### **Petrolatum:**

Test Type : Buehler Test

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

Routes of exposure : Skin contact  
Species : Guinea pig  
Result : negative  
Remarks : Based on data from similar materials

### Zinc oxide:

Test Type : Maximization Test  
Routes of exposure : Skin contact  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : negative

### Benzyl alcohol:

Test Type : Human repeat insult patch test (HRIPT)  
Routes of exposure : Skin contact  
Species : Humans  
Result : positive

Assessment : Probability or evidence of low to moderate skin sensitization rate in humans

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Bismuth hydroxide nitrate oxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative

Test Type: Chromosome aberration test in vitro  
Method: OECD Test Guideline 473  
Result: negative

#### Petrolatum:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

### Zinc oxide:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative
- Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: equivocal
- Test Type: Chromosome aberration test in vitro  
Result: equivocal
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 474  
Result: negative
- Test Type: Mutagenicity (in vivo mammalian bone-marrow  
cytogenetic test, chromosomal analysis)  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Result: positive
- Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative
- Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ  
cell mutagen.

### Benzyl alcohol:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo  
cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Components:

#### Petrolatum:

- Species : Rat

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

Application Route : Ingestion  
Exposure time : 2 Years  
Result : negative

### Zinc oxide:

Species : Mouse  
Application Route : Ingestion  
Exposure time : 1 Years  
Result : negative  
Remarks : Based on data from similar materials

### Benzyl alcohol:

Species : Mouse  
Application Route : Ingestion  
Exposure time : 103 weeks  
Method : OECD Test Guideline 451  
Result : negative

**IARC** No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA** No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP** No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

### Components:

#### Bismuth hydroxide nitrate oxide:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Ingestion  
Method: OECD Test Guideline 414  
Result: negative

#### Petrolatum:

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: Skin contact  
Result: negative  
Remarks: Based on data from similar materials

### **Zinc oxide:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Rat  
Application Route: inhalation (dust/mist/fume)  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

### **Benzyl alcohol:**

Effects on fertility : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: Ingestion  
Result: negative

### **STOT-single exposure**

Not classified based on available information.

### **STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

### **Components:**

#### **Bismuth hydroxide nitrate oxide:**

Target Organs : Central nervous system  
Assessment : Causes damage to organs through prolonged or repeated exposure.

#### **Zinc oxide:**

Assessment : No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

### Repeated dose toxicity

#### Components:

##### **Petrolatum:**

Species : Rat  
NOAEL : 5,000 mg/kg  
Application Route : Ingestion  
Exposure time : 2 y

##### **Zinc oxide:**

Species : Rat, male  
NOAEL : 0.0015 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 3 Months  
Method : OECD Test Guideline 413

##### **Benzyl alcohol:**

Species : Rat  
NOAEL : 1.072 mg/l  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 28 Days  
Method : OECD Test Guideline 412

### Aspiration toxicity

Not classified based on available information.

### Experience with human exposure

#### Product:

Ingestion : Symptoms: The absorption of this product into the body may lead to the formation of methaemoglobine that, in sufficient concentration, causes cyanosis., May cause, Neurological disorders, Blood disorders, blood effects, central nervous system effects, Methaemoglobinemia

#### Components:

##### **Bismuth hydroxide nitrate oxide:**

Ingestion : Target Organs: Blood  
Symptoms: Methaemoglobinemia  
Target Organs: Central nervous system  
Symptoms: Neurological disorders

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### **Bismuth hydroxide nitrate oxide:**

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 137 mg/l

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 137 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

NOELR (Pseudokirchneriella subcapitata (green algae)): > 137 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201

### **Petrolatum:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
Exposure time: 21 d  
Test substance: Water Accommodated Fraction  
Remarks: Based on data from similar materials

### **Zinc oxide:**

Toxicity to fish : LC50 : > 0.1 - 1 mg/l  
Exposure time: 96 h  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.136 mg/l

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

Exposure time: 72 h

NOEC (Pseudokirchneriella subcapitata (green algae)): > 0.01 - 0.1 mg/l

Exposure time: 72 h

Remarks: Based on data from similar materials

Toxicity to fish (Chronic toxicity) : NOEC (Jordanella floridae (flagfish)): > 0.01 - 0.1 mg/l  
Exposure time: 14 Weeks  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Ceriodaphnia dubia (water flea)): > 0.01 - 0.1 mg/l  
Exposure time: 7 d  
Remarks: Based on data from similar materials

### **Benzyl alcohol:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 460 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 230 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 770 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 310 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 51 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

### **Persistence and degradability**

#### **Components:**

##### **Petrolatum:**

Biodegradability : Result: Not readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: The test was conducted according to guideline  
Based on data from similar materials

##### **Benzyl alcohol:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 92 - 96 %  
Exposure time: 14 d

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version 6.2      Revision Date: 05/09/2026      SDS Number: 656848-00024      Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

---

### Bioaccumulative potential

#### Components:

##### Zinc oxide:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 78 - 2,060

##### Benzyl alcohol:

Partition coefficient: n-octanol/water : log Pow: 1.05

##### Mobility in soil

No data available

##### Other adverse effects

No data available

##### Endocrine disrupting properties

No data available

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of in accordance with local regulations.  
Do not dispose of waste into sewer.  
Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.  
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)  
Class : 9  
Packing group : III  
Labels : 9  
Environmentally hazardous : yes

#### IATA-DGR

UN/ID No. : UN 3077  
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.  
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)  
Class : 9  
Packing group : III  
Labels : Miscellaneous  
Packing instruction (cargo aircraft) : 956  
Packing instruction (passen- : 956

---

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

ger aircraft)  
Environmentally hazardous : yes

### IMDG-Code

UN number : UN 3077  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,  
N.O.S.  
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Domestic regulation

#### 49 CFR

UN/ID/NA number : UN 3077  
Proper shipping name : Environmentally hazardous substance, solid, n.o.s.  
(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)  
Class : 9  
Packing group : III  
Labels : CLASS 9  
ERG Code : 171  
Marine pollutant : yes(Zinc oxide, 2,6-Di-tert-butyl-p-cresol)  
Remarks : Above applies only to containers over 119 gallons (450 liters)  
in case of liquids, or 882 lbs. (400 kg) in case of solids.  
Shipment by ground under DOT is non-regulated for non-bulk  
packaging; however it may be shipped per the applicable  
hazard classification to facilitate multi-modal transport  
involving ICAO (IATA) or IMO.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Respiratory or skin sensitization  
Specific target organ toxicity (single or repeated exposure)

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

Zinc oxide	1314-13-2	>= 5 - < 10 %
------------	-----------	---------------

### US State Regulations

#### Pennsylvania Right To Know

Bismuth hydroxide nitrate oxide	1304-85-4
Petrolatum	8009-03-8
Zinc oxide	1314-13-2
Oleic acid	112-80-1
Benzyl alcohol	100-51-6

#### California List of Hazardous Substances

Petrolatum	8009-03-8
Zinc oxide	1314-13-2

#### California Permissible Exposure Limits for Chemical Contaminants

Petrolatum	8009-03-8
Zinc oxide	1314-13-2

#### The ingredients of this product are reported in the following inventories:

AICS	: not determined
CA. DSL	: not determined
CN IECSC	: not determined

---

## SECTION 16. OTHER INFORMATION

### Further information

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation


Version  
6.2

Revision Date:  
05/09/2026

SDS Number:  
656848-00024

Date of last issue: 12/06/2025  
Date of first issue: 05/02/2016

### NFPA 704:



### HMIS® IV / CED:

HEALTH	*	3
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA Z-1 / TWA	:	8-hour time weighted average
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

# SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



## Bismuth Subnitrate Formulation

Version	Revision Date:	SDS Number:	Date of last issue: 12/06/2025
6.2	05/09/2026	656848-00024	Date of first issue: 05/02/2016

---

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/09/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8