

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

SECTION 1. IDENTIFICATION

Product name : Guanidine Hydrochloride Formulation

Manufacturer or supplier's details

Company name of supplier : Merck & Co., Inc
Address : 126 E. Lincoln Avenue
Rahway, New Jersey U.S.A. 07065
Telephone : 908-740-4000
Emergency telephone : 1-908-423-6000
E-mail address : EHSDATASTEWARD@merck.com

Recommended use of the chemical and restrictions on use

Recommended use : Pharmaceutical
Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Hazards for the product as supplied

Acute toxicity (Oral) : Category 4
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity : Category 1 (Nervous system, Bone marrow, Kidney)
- repeated exposure

Other hazards

None known.

Hazards associated with a change in physical form:

| Conditions | Hazards |
|---|--|
| If small particles are generated during further processing, handling or by other means. | May form combustible dust concentrations in air. |

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H302 Harmful if swallowed.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H372 Causes damage to organs (Nervous system, Bone mar-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

row, Kidney) through prolonged or repeated exposure.

Precautionary Statements

- Prevention:**
P260 Do not breathe dust.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, eye protection and face protection.
- Response:**
P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel unwell. Rinse mouth.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical attention.
P337 + P313 If eye irritation persists: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
- Disposal:**
P501 Dispose of contents and container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS No./Unique ID | Concentration (% w/w) | Trade secret |
|----------------------|-------------------|-----------------------|--------------|
| Cellulose | 9004-34-6* | >= 30 - <= 60 | TSC |
| Guanidinium chloride | 50-01-1* | >= 15 - <= 40 | TSC |
| Silicon dioxide | 7631-86-9* | >= 1 - <= 5 | TSC |
| Magnesium stearate | 557-04-0* | >= 0.5 - <= 1.5 | TSC |

* Indicates that the identifier is a CAS No.

TSC- the actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

- In case of skin contact : Get medical attention if symptoms occur.
: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.
- If swallowed : If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.
Get medical attention.
Rinse mouth thoroughly with water.
Never give anything by mouth to an unconscious person.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
Causes damage to organs through prolonged or repeated exposure.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : None known.
- Specific hazards during fire fighting : Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides
Nitrogen oxides (NO_x)
Chlorine compounds
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment : In the event of fire, wear self-contained breathing apparatus.
-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/06/2025 |
| 11.1 | 05/09/2026 | 438992-00024 | Date of first issue: 01/06/2016 |

for fire-fighters Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Sweep up or vacuum up spillage and collect in suitable container for disposal. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- Technical measures : Static electricity may accumulate and ignite suspended dust causing an explosion. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Do not get on skin or clothing. Do not breathe dust. Do not swallow. Do not get in eyes. Wash skin thoroughly after handling. Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment. Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Materials to avoid : Store in accordance with the particular national regulations.
: Do not store with the following product types:
Strong oxidizing agents
Self-reactive substances and mixtures
Organic peroxides
Explosives
Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3

15 mg/m³
Value type (Form of exposure): TWA (total dust)
Basis: OSHA Z-3

5 mg/m³
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3

15 Million particles per cubic foot
Value type (Form of exposure): TWA (respirable fraction)
Basis: OSHA Z-3

Dust, nuisance dust and particulates 10 mg/m³
Value type (Form of exposure): PEL (Total dust)
Basis: CAL PEL

5 mg/m³
Value type (Form of exposure): PEL (respirable dust fraction)
Basis: CAL PEL

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------|-----------|-------------------------------|--|-----------|
| Cellulose | 9004-34-6 | TWA | 10 mg/m ³ | ACGIH |
| | | TWA (Respirable) | 5 mg/m ³ | NIOSH REL |
| | | TWA (total) | 10 mg/m ³ | NIOSH REL |
| | | TWA (total dust) | 15 mg/m ³ | OSHA Z-1 |
| | | TWA (respirable fraction) | 5 mg/m ³ | OSHA Z-1 |
| Guanidinium chloride | 50-01-1 | TWA | 600 µg/m ³ (OEB 2) | Internal |
| Silicon dioxide | 7631-86-9 | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

| | | | | |
|--------------------|----------|-------------------------------------|---|-----------|
| | | TWA (Dust) | 80 mg/m ³ / %SiO ₂ (Silica) | OSHA Z-3 |
| | | TWA | 6 mg/m ³ (Silica) | NIOSH REL |
| Magnesium stearate | 557-04-0 | TWA (Inhalable particulate matter) | 10 mg/m ³ | ACGIH |
| | | TWA (Respirable particulate matter) | 3 mg/m ³ | ACGIH |

Engineering measures : Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations. Apply measures to prevent dust explosions. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : Chemical-resistant gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : If exposure to chemical is likely during typical use, provide

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/06/2025 |
| 11.1 | 05/09/2026 | 438992-00024 | Date of first issue: 01/06/2016 |

eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|--|---|---|
| Appearance | : | powder |
| Color | : | No data available |
| Odor | : | No data available |
| Odor Threshold | : | No data available |
| pH | : | No data available |
| Melting point/freezing point | : | No data available |
| Initial boiling point and boiling range | : | No data available |
| Flash point | : | Not applicable |
| Evaporation rate | : | Not applicable |
| Flammability (solid, gas) | : | May form explosive dust-air mixture during processing, handling or other means. |
| Flammability (liquids) | : | Not applicable |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapor pressure | : | Not applicable |
| Relative vapor density | : | Not applicable |
| Relative density | : | No data available |
| Density | : | No data available |
| Solubility(ies) Water solubility | : | No data available |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Autoignition temperature | : | No data available |
| Decomposition temperature | : | No data available |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/06/2025 |
| 11.1 | 05/09/2026 | 438992-00024 | Date of first issue: 01/06/2016 |

Viscosity
Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle characteristics
Particle size : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : May form explosive dust-air mixture during processing, handling or other means.
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.
Avoid dust formation.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity : Acute toxicity estimate: 1,330 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 8.62 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Components:

Cellulose:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Guanidinium chloride:

Acute oral toxicity : LD50 (Rat): 474.6 mg/kg
LD50 (Mouse): 571 mg/kg

Acute inhalation toxicity : LC50 (Rat): 3.181 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 5,110 mg/kg
Method: OECD Test Guideline 401
Remarks: The test was conducted according to guideline

Acute inhalation toxicity : LC50 (Rat): > 5.198 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Remarks: The test was conducted according to guideline

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No test guideline followed

Magnesium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Method: OECD Test Guideline 423
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:

Guanidinium chloride:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Species : Rabbit
Result : Skin irritation

Silicon dioxide:

Species : Rabbit
Method : OECD Test Guideline 404
Result : No skin irritation
Remarks : The test was conducted according to guideline

Magnesium stearate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Guanidinium chloride:

Result : Irritation to eyes, reversing within 21 days
Remarks : Based on national or regional regulation.

Silicon dioxide:

Species : Rabbit
Result : No eye irritation
Method : OECD Test Guideline 405
Remarks : The test was conducted equivalent or similar to guideline

Magnesium stearate:

Species : Rabbit
Result : No eye irritation
Remarks : Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:

Guanidinium chloride:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Result : negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Silicon dioxide:

Test Type : Buehler Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : The test was conducted according to guideline

Magnesium stearate:

Test Type : Maximization Test
Routes of exposure : Skin contact
Species : Guinea pig
Method : OECD Test Guideline 406
Result : negative
Remarks : Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Components:

Cellulose:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Mouse
Application Route: Ingestion
Result: negative

Guanidinium chloride:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Result: negative

Silicon dioxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative
Remarks: The test was conducted equivalent or similar to
guideline

Test Type: In vitro mammalian cell gene mutation test
Method: OECD Test Guideline 476

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Result: negative
Remarks: The test was conducted according to guideline

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Genotoxicity in vivo : Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 475
Result: negative
Remarks: The test was conducted equivalent or similar to guideline

Magnesium stearate:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative
Remarks: Based on data from similar materials

Test Type: Chromosome aberration test in vitro
Method: OECD Test Guideline 473
Result: negative
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)
Result: negative
Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Components:

Cellulose:

Species : Rat
Application Route : Ingestion
Exposure time : 72 weeks
Result : negative

Silicon dioxide:

Species : Rat
Application Route : Ingestion
Exposure time : 103 weeks
Result : negative
Remarks : No test guideline followed

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Result: negative
Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Ingestion
Result: negative
Remarks: Based on data from similar materials

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Nervous system, Bone marrow, Kidney) through prolonged or repeated exposure.

Components:

Guanidinium chloride:

Routes of exposure : Ingestion
Target Organs : Nervous system, Kidney, Bone marrow
Assessment : Causes damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

Components:

Cellulose:

Species : Rat
NOAEL : $\geq 9,000$ mg/kg
Application Route : Ingestion
Exposure time : 90 Days

Guanidinium chloride:

Species : Rat
NOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Method : OECD Test Guideline 408

Silicon dioxide:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 26 Weeks
Method : OECD Test Guideline 408
Remarks : The test was conducted equivalent or similar to guideline

Species : Rat
NOAEL : $> 2,000$ mg/kg
Application Route : Skin contact

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Exposure time : 13 Weeks
Method : OECD Test Guideline 411
Remarks : The test was conducted according to guideline

Magnesium stearate:

Species : Rat
NOAEL : > 100 mg/kg
Application Route : Ingestion
Exposure time : 90 Days
Remarks : Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

Guanidinium chloride:

Ingestion : Symptoms: tingling, numbness, anorexia, Diarrhea

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Cellulose:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 100 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Guanidinium chloride:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 1,758 mg/l
Exposure time: 48 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 70.2 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 11.8 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

NOEC (Pseudokirchneriella subcapitata (green algae)): 6.3 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to fish (Chronic tox- : NOEC (Pimephales promelas (fathead minnow)): 181 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

icity) Exposure time: 35 d
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2.9 mg/l
Exposure time: 21 d
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): 7,125 mg/l
Exposure time: 18 h

Silicon dioxide:

Toxicity to fish : LL50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: The test was conducted according to guideline

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 202
Remarks: The test was conducted according to guideline

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline

NOELR (Desmodesmus subspicatus (green algae)): 10,000 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: The test was conducted according to guideline

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : (Daphnia magna (Water flea)): 132.7 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: The test was conducted according to guideline

Toxicity to microorganisms : NOEC (activated sludge): 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209
Remarks: The test was conducted according to guideline

Magnesium stearate:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 100 mg/l
Exposure time: 48 h
Method: DIN 38412

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

Version 11.1 Revision Date: 05/09/2026 SDS Number: 438992-00024 Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1 mg/l
Exposure time: 47 h
Test substance: Water Accommodated Fraction
Method: Directive 67/548/EEC, Annex V, C.2.
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials
No toxicity at the limit of solubility.

NOELR (Pseudokirchneriella subcapitata (green algae)): > 1 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to microorganisms : EC10 (Pseudomonas putida): > 100 mg/l
Exposure time: 16 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Persistence and degradability

Components:

Cellulose:

Biodegradability : Result: Readily biodegradable.

Guanidinium chloride:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 56 d
Method: OECD Test Guideline 301C

Magnesium stearate:

Biodegradability : Result: Not biodegradable
Remarks: Based on data from similar materials

Bioaccumulative potential

Components:

Guanidinium chloride:

Partition coefficient: n- : log Pow: < -1.7

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/06/2025 |
| 11.1 | 05/09/2026 | 438992-00024 | Date of first issue: 01/06/2016 |

octanol/water

Magnesium stearate:

Partition coefficient: n- : log Pow: > 4
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

Endocrine disrupting properties

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with local regulations.
Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste
handling site for recycling or disposal.
If not otherwise specified: Dispose of as unused product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to IMO instruments

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/06/2025 |
| 11.1 | 05/09/2026 | 438992-00024 | Date of first issue: 01/06/2016 |

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

| | |
|----------------------|-----------|
| Cellulose | 9004-34-6 |
| Guanidinium chloride | 50-01-1 |
| D-Mannitol | 69-65-8 |
| Silicon dioxide | 7631-86-9 |

California List of Hazardous Substances

| | |
|-----------------|-----------|
| Silicon dioxide | 7631-86-9 |
|-----------------|-----------|

California Permissible Exposure Limits for Chemical Contaminants

| | |
|--------------------|-----------|
| Cellulose | 9004-34-6 |
| Silicon dioxide | 7631-86-9 |
| Magnesium stearate | 557-04-0 |

The ingredients of this product are reported in the following inventories:

| | |
|----------|------------------|
| AICS | : not determined |
| CA. DSL | : not determined |
| CN IECSC | : not determined |

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation


Version
11.1

Revision Date:
05/09/2026

SDS Number:
438992-00024

Date of last issue: 12/06/2025
Date of first issue: 01/06/2016

NFPA 704:



HMIS® IV / CED:

| | | |
|-----------------|---|---|
| HEALTH | * | 3 |
| FLAMMABILITY | | 3 |
| PHYSICAL HAZARD | | 0 |

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

| | | |
|-----------------|---|---|
| ACGIH | : | USA. ACGIH Threshold Limit Values (TLV) |
| CAL PEL | : | California permissible exposure limits for chemical contaminants (Title 8, Article 107) |
| NIOSH REL | : | USA. NIOSH Recommended Exposure Limits |
| OSHA Z-1 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| OSHA Z-3 | : | USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts |
| ACGIH / TWA | : | 8-hour, time-weighted average |
| CAL PEL / PEL | : | Permissible exposure limit |
| NIOSH REL / TWA | : | Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek |
| OSHA Z-1 / TWA | : | 8-hour time weighted average |
| OSHA Z-3 / TWA | : | 8-hour time weighted average |

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardization; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organization for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Pre-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Guanidine Hydrochloride Formulation

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 12/06/2025 |
| 11.1 | 05/09/2026 | 438992-00024 | Date of first issue: 01/06/2016 |

vention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorization and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/09/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8